

HELUCONTROL® JZ-510-HMH LS0H GREY



flexible, number coded, halogen-free, meter marking, increased flame retardancy Cca

Part no.	No. cores x cross-sec. mm ²	Outer-ø mm	Cu-weight kg/km	Weight kg/km, approx.
11021648	2 x 1	5.6	19.2	63.0
11021649	3 G 1	6.1	29.0	74.0
11021650	3 x 1	6.1	29.0	74.0
11021651	4 G 1	6.7	38.4	90.0
11021652	4 x 1	6.7	38.4	90.0
11021653	5 G 1	7.5	48.0	109.0
11021654	7 G 1	8.1	67.0	151.0
11021655	12 G 1	10.9	115.0	243.0
11021656	18 G 1	12.9	173.0	361.0
11021657	25 G 1	15.4	240.0	496.0
11021658	2 x 1.5	6.4	29.0	70.0
11021659	3 G 1.5	6.8	43.0	94.0
11021660	3 x 1.5	6.8	43.0	94.0
11021661	4 G 1.5	7.6	58.0	112.0
11021662	4 x 1.5	7.6	58.0	112.0

Part no.	No. cores x cross-sec. mm ²	Outer-ø mm	Cu-weight kg/km	Weight kg/km, approx.
11021663	5 G 1.5	8.3	72.0	141.0
11021664	7 G 1.5	9.2	101.0	191.0
11021665	12 G 1.5	12.4	173.0	311.0
11021666	18 G 1.5	14.8	259.0	450.0
11021667	25 G 1.5	17.6	360.0	630.0
11021668	3 G 2.5	8.3	72.0	151.0
11021669	4 G 2.5	9.3	96.0	181.0
11021670	5 g 2.5	10.1	120.0	224.0
11021671	7 G 2.5	11.2	168.0	316.0
11021672	12 G 2.5	15.3	288.0	499.0
11021673	18 G 2.5	18.2	432.0	769.0
11021674	25 g 2.5	21.6	600.0	1047.0
11021675	4 G 4	10.9	154.0	299.0
11021676	4 G 6	13.2	230.0	429.0
11021677	4 G 10	16.6	384.0	708.0