

# SOLARFLEX® MB LS0H Cca



## TECHNICAL DATA

Cross-linked single core cable in alignment with EN 50618

|  |  |
|--|--|
| Temperature range                                  | fixed -40°C to +90°C   |
| Permissible operating temperature of the conductor | +120°C   |
| Nominal voltage                                    | AC U <sub>0</sub> /U 1000/1000 V<br>DC U <sub>0</sub> /U 1500/1500 V |
| Test voltage                                       | 6500 V   |
| Minimum bending radius                             | 5 x outer-Ø  |

## CABLE STRUCTURE

- Copper wire tinned, finely stranded acc. to DIN VDE 0295 Class 5 / IEC 60228 Class 5
- Core insulation: cross-linked compound
- x = without protective conductor
- Outer sheath: thermoset compound
- Sheath colour: see table

## PROPERTIES

- resistant to: UV radiation, ozone, weathering effects, water
- for outdoor use
- direct burial
- halogen-free

## TESTS

- halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1
- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- smoke density acc. to DIN VDE 0482-1034-1+2 / DIN EN 61034-1+2 / IEC 61034-1+2
- UV-resistant acc. to DIN VDE 0283-618 / DIN EN 50618 Appendix E
- ozone-resistant acc. to DIN VDE 0283-618 / DIN EN 50618
- weather-resistant acc. to DIN VDE 0283-618 / DIN EN 50618 Appendix E
- DC Voltage resistance of the insulation acc. to DIN VDE 0283-618 / DIN EN 50618 Tab. 2
- CPR-class: Cca s1a,d0,a2

## APPLICATION

SOLARFLEX® MB LS0H Cca is used for wiring solar modules. Suitable for direct burial; recommendation: laying in pipes. Not suitable for permanent installation in water. The maximum permissible DC voltage of the system in which the cable is installed must not exceed 1.8 kV. The cable is suitable for use in and on devices and systems with protective insulation (protection class II).

## NOTES

- the conductor is metrically (mm<sup>2</sup>) constructed, AWG numbers are approximated, and are for reference only

| No. cores x cross-sec. mm <sup>2</sup> | AWG, approx. | Outer-Ø min - max mm | Cu-weight kg/km | Weight kg/km, approx. | blue Part no.   | red Part no.    | black Part no.  |
|--|--------------|----------------------|-----------------|-----------------------|-----------------|-----------------|-----------------|
| 1 x 4                                  | 12           | 5,0 - 6,0            | 38,4            | 60,0                  | <b>18126081</b> | <b>18126085</b> | <b>18126083</b> |
| 1 x 6                                  | 10           | 5,5 - 6,5            | 57,6            | 80,0                  | <b>18126082</b> | <b>18126086</b> | <b>18126084</b> |
| 1 x 10                                 | 8            | 6,9 - 7,7            | 96,0            | 126,0                 | -               | -               | <b>18126075</b> |
| 1 x 16                                 | 6            | 7,7 - 8,5            | 153,6           | 170,0                 | -               | -               | <b>18126076</b> |
| 1 x 25                                 | 4            | 10,0 - 10,8          | 240,0           | 270,0                 | -               | -               | <b>18126077</b> |
| 1 x 35                                 | 2            | 11,5 - 12,3          | 336,0           | 365,0                 | -               | -               | <b>18126078</b> |