

HELUCONTROL® JZ-510-HMH UV / HELUCONTROL® OZ-510-HMH UV

highly flame-retardant



HELUKABEL® HELUCONTROL® JZ-510-HMH UV CE

TECHNICAL DATA

Control and connection cable in alignment DIN VDE 0285-525-2-51 / DIN EN 50525-2-51, DIN VDE 0285-525-3-11 / DIN EN 50525-3-11

Temperature range	flexible -25°C to +70°C fixed -40°C to +70°C
Nominal voltage	AC U ₀ /U 300/500 V
Test voltage core/core	4000 V
Minimum bending radius	flexible 12,5x Outer-Ø fixed 4x Outer-Ø

CABLE STRUCTURE

- Copper wire bare, finely stranded acc. to DIN VDE 0295 Class 5 / IEC 60228 Class 5
- Core insulation: halogen-free polymer acc. to DIN VDE 0207-363-7 / DIN EN 50363-7 (compound type TI6)
- Core identification acc. to DIN VDE 0293-334, black cores with consecutive labeling in white digits
- Protective conductor: starting with 3 cores, G = with protective conductor GN-YE, in the outer layer (JZ), x = without protective conductor (OZ)
- Cores stranded in layers with optimal lay lengths
- Outer sheath: halogen-free polymer acc. to DIN VDE 0207-363-8 / DIN EN 50363-8 (compound type TM7)
- Sheath colour: grey (RAL 7001)
- Length marking: in metres

PROPERTIES

- resistant to: UV radiation, weathering effects
- largely resistant to: oil
- for outdoor use

- halogen-free
- the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

TESTS

- halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1
- corrosiveness of combustion gases acc. to DIN VDE 0482-754-2 / DIN EN 60754-2 / IEC 60754-2
- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- bundle fire test acc. to DIN VDE 0482-332-3-24 / DIN EN 60332-3-24 / IEC 60332-3-24
- smoke density acc. to DIN VDE 0482-1034-1+2 / DIN EN 61034-1+2 / IEC 61034-1+2
- UV-resistant acc. to DIN EN ISO 4892-2
- weather-resistant acc. to DIN EN ISO 4892-2
- CPR-class: Cca s1a d1 a1

APPLICATION

Control and connection cable in tool machinery, conveyor belts, production lines, plant construction, in air-conditioning devices, in metallurgical, steel and rolling mills. For fixed installation and flexible applications with occasional, not constantly recurring free movement without forced motion, without tensile stress and for medium mechanical stress. The cable is suitable for use in dry, damp and wet locations, outdoors (fixed installation) and on plaster.

NOTES

- the conductor is metrically (mm²) constructed, AWG numbers are approximated, and are for reference only

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
18126360	2 x 0.5	20	4.8	9.6	43.0
18126361	3 x 0.5	20	5.1	14.4	50.0
18126362	3 G 0.5	20	5.1	14.4	50.0
18126363	4 x 0.5	20	5.5	19.2	60.0
18126364	4 G 0.5	20	5.5	19.2	60.0
18126365	5 x 0.5	20	6.2	24.0	71.0
18126366	5 G 0.5	20	6.2	24.0	71.0
18126367	7 x 0.5	20	6.7	33.6	84.0
18126368	7 G 0.5	20	6.7	33.6	84.0
18126369	8 x 0.5	20	7.4	38.4	101.0
18126370	8 G 0.5	20	7.4	38.4	101.0
18126371	10 G 0.5	20	8.6	48.0	121.0
18126372	12 G 0.5	20	9.1	57.6	142.0
18126373	16 G 0.5	20	10.0	76.8	183.0
18126374	18 G 0.5	20	10.7	86.4	204.0
18126375	25 G 0.5	20	12.6	120.0	283.0

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
18126376	2 x 0.75	19	5.3	14.4	47.0
18126377	3 x 0.75	19	5.6	21.6	56.0
18126378	3 G 0.75	19	5.6	21.6	56.0
18126379	4 x 0.75	19	6.3	28.8	69.0
18126380	4 G 0.75	19	6.3	28.8	69.0
18126381	5 x 0.75	19	6.9	36.0	83.0
18126382	5 G 0.75	19	6.9	36.0	83.0
18126383	7 x 0.75	19	7.7	50.4	114.0
18126384	7 G 0.75	19	7.7	50.4	114.0
18126385	8 x 0.75	19	8.3	57.6	136.0
18126386	8 G 0.75	19	8.3	57.6	136.0
18126387	10 G 0.75	19	9.8	72.0	172.0
18126388	12 G 0.75	19	10.1	86.4	183.0
18126389	16 G 0.75	19	11.4	115.2	241.0
18126390	18 G 0.75	19	12.2	129.6	266.0
18126391	25 G 0.75	19	14.3	180.0	374.0

HELUCONTROL® JZ-510-HMH UV / HELUCONTROL® OZ-510-HMH UV

highly flame-retardant



Part no.	No. cores x cross-sec. mm²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
18126392	2 x 1	18	5.6	19.2	63.0
18126393	3 x 1	18	6.1	28.8	74.0
18126394	3 G 1	18	6.1	28.8	74.0
18126395	4 x 1	18	6.7	38.4	90.0
18126396	4 G 1	18	6.7	38.4	90.0
18126397	5 x 1	18	7.5	48.0	109.0
18126398	5 G 1	18	7.5	48.0	109.0
18126399	7 x 1	18	8.1	67.2	151.0
18126400	7 G 1	18	8.1	67.2	151.0
18126401	8 x 1	18	9.0	76.8	184.0
18126402	8 G 1	18	9.0	76.8	184.0
18126403	10 G 1	18	10.6	96.0	224.0
18126404	12 G 1	18	10.9	115.2	243.0
18126405	16 G 1	18	12.3	153.6	314.0
18126406	18 G 1	18	12.9	172.8	361.0
18126407	25 G 1	18	15.4	240.0	496.0
18126408	2 x 1.5	16	6.4	28.8	70.0
18126409	3 G 1.5	16	6.8	43.0	94.0
18126410	4 G 1.5	16	7.6	57.6	112.0
18126411	5 G 1.5	16	8.3	72.0	141.0

Part no.	No. cores x cross-sec. mm²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
18126412	7 G 1.5	16	9.2	100.8	191.0
18126413	8 G 1.5	16	9.9	115.2	224.0
18126414	10 G 1.5	16	12.0	144.0	282.0
18126415	12 G 1.5	16	12.4	172.8	311.0
18126416	16 G 1.5	16	13.9	230.4	392.0
18126417	18 G 1.5	16	14.8	259.2	450.0
18126418	25 G 1.5	16	17.6	360.0	630.0
18126419	2 x 2.5	14	7.8	48.0	118.0
18126420	3 G 2.5	14	8.3	72.0	151.0
18126421	4 G 2.5	14	9.3	96.0	181.0
18126422	5 G 2.5	14	10.1	120.0	224.0
18126423	7 G 2.5	14	11.2	168.0	316.0
18126424	10 G 2.5	14	14.8	240.0	451.0
18126425	12 G 2.5	14	15.3	288.0	499.0
18126426	16 G 2.5	14	17.1	384.0	720.0
18126427	18 G 2.5	14	18.2	432.0	769.0
18126428	25 G 2.5	14	21.6	600.0	1047.0
18126429	2 x 4	12	9.2	76.8	199.0
18126430	3 G 4	12	9.8	115.2	247.0
18126431	4 G 4	12	10.9	153.6	299.0
18126432	5 G 4	12	12.1	192.0	369.0